## INFLUENCE OF ATMOSPHERIC TURBULENCE ON PLANETARY TRANSCEIVER LASER RANGING.

D. Dirkx<sup>1</sup>, R.Noomen<sup>1</sup>, I. Prochazka<sup>2</sup>, S. Bauer<sup>3</sup>, L.L.A. Vermeersen<sup>1</sup>

<sup>1</sup>Delft University of Technology, The Netherlands (<u>d.dirkx@tudelft.nl</u>, Kluyverweg 1, 2629HS, Delft, The Netherlands), <sup>2</sup>Czech Technical University in Prague, Czech Republic, <sup>3</sup>DLR Berlin, Germany

**Introduction:** We investigate the influence of atmospheric turbulence on the performance of the uplink of a planetary transceiver laser ranging system using a single photon detector. We numerically combine the influence of turbulence in the mean intensity profile variations, scintillation, beam-wander induced pointing errors [1],[2] and stochastic time-of-flight variations [3]. Thereby, we map the intensity variations due to turbulence to variations in the probability distribution of the arrival time of the 1st photon in a laser pulse, which influences the range measurement error probability distribution..The turbulence models are applied to assess the influence on single-pass range accuracy and precision statistics, as well as the parameter estimation quality of a Phobos Laser Ranging (PLR) mission [4].

Range measurement errors: The difference in range measurement error between weak and strong turbulence is 3-4 mm in a PLR concept. This indicates that turbulence is a potentially important contributor to the error budget of interplanetary laser ranging missions, which aim at mm-level accuracy and precision. The single-shot precision is generally weakly influenced by turbulence, but strong turbulence is found to cause a strong decrease in detected pulse fraction, reducing normal point precision. We show that a tradeoff between range accuracy and precision must be made when selecting laser system parameters, which is influenced by atmospheric turbulence effects. By consistently operating at the single-photon signal strength level, accuracy variations can be largely removed, at the expense of normal point precision, due to the reduced detection probability.

**Parameter estimation influence** We perform parameter estimations of Phobos initial state and observation biases using simulated measurements with and without turbulence, using a daily periodic turbulence strength model. We show that the parameter estimation quality is degraded significantly below that of the turbulence-free case only in the presence of strong turbulence.

## Acknowledgements

Part of this work is financed by the FP7 ESPaCE project, financially supported by the EC FP7 Grant Agreement 263466.

## **References:**

- [1] Andrews, L. C., Phillips, R. L., Hopen, C. Y., (2000), Opt. Eng. 39, 3272-3280.
- [2] Andrews, L. C. et al., (2006), Opt. Eng. 45 (7), 076001.
- [3] Kral, K., Prochazka, I., Hamal, K., (2005) Opt. Lett. 30 (14), 1767-1769.
- [4] Turyshev et al. Dec. (2010) Exp. Astron. 28, 209-249.